SCOPE OF ACCREDITATION TO ISO/IEC 17025:2017

ELEMENT MATERIALS TECHNOLOGY CANADA INC.*
Mississauga Laboratory
2395 Speakman Drive
Mississauga, Ontario, Canada L5K 1B3
Luiz Rios Phone: 905-822-4111 ext. 10282

Test Method:	**Test Description:**
AAMA 1304	Voluntary specification for forced entry resistance of side-hinged door systems
AAMA 1503	Voluntary test method for thermal transmittance and condensation resistance of windows, doors and glazed wall sections (CRF only)
ANSI Z97.1	Standard for safety glazing materials used in buildings safety performance specifications and methods of test

Test Method:

Test Method:	Test Description:
CGSB 75.1-M88	Tile - cerami i9 Tw 10.98 -0o52 650.98 -0 s0598 -0 0 10.98 231.54 6(0.4

Test Method:	**Test Description:**
CAN/ULC S711.1	Standard for thermal insulation – bead-applied two component polyurethane air sealant foam - part 1: material specification (except C177 and E514)
CAN/ULC S711.2	Standard for thermal insulation – bead-applied two component polyurethane air sealant foam – part 2: installation
CAN/ULC S712.1	Standard for thermal insulation - light density - open cell spray applied semi-rigid polyurethane foam - material specification
CAN/ULC S743.1	STANDARD FOR THERMAL INSULATION – LOW PRESSURE APPLIED TWO COMPONENT SPRAY POLYURETHANE FOAM, PART 1: MATERIAL SPECIFICATION
CAN/ULC S770	Standard test method for determination of long-term thermal resistance of closed-cell thermal insulating foams
ICC ES AC02	Reflective insulation (test methods referenced in sections 3.0)